

GENERAL

SPECIFICATIONS





Lift Capacity: 15,000 lbs

Tow Mast: Removable side mast assembly with lever hydraulically operated from cab.

Tow Mast Lift Height: -9" to +45"

Tow Hitch: 2 15/16" - 30,000 lb capacity ball hitch (set to customer specs)

ENGINE

MAST

-John Deere Power Tech EWX, 74HP (55KW) @2400 **RPM**

-14.7 Liter Oil Pan

-12 V Starter

TRANSMISSION

-12 V Alternator 75 Amp

Synchromesh Power Shuttle Transmission with Torque Converter. Independent high capacity oil cooler.

TRAVEL SPEED

20 mph (forward and reverse)

STEERING Hydrostatic power steering with 2 double acting

steer cylinders on 2 wheel drive machines.

STEER AXLE

Heavy duty industrial center pivot mount with 2" King Pins and 3" Spindles.



Scan here to find us on Instagram!





Parking Brake

The park brake is lever operated with a disctype caliper. (Disc located on transmission)

Hydraulics

30.5 GPM Capacity @ 2200 PSI RPM crankshaft driven gear type 2 stage pump, pre-set relief valve, one master cylinder and one mast side shift cylinder.

Instruments

Onboard computer monitors oil pressure, fuel level, volt meter, park brake warning light., and hour meter. All units are equipped with a back-up alarm.



Check us out on Facebook!



Drive Axle

Heavy duty drive axle consists of double reduction matched pinion and bevel gear with outboard planetary gear with final reduction.

Brakes

Foot operated, hydraulic actuated wet disc brake sealed in oil (246 sq. in. total braking area). Brakes operated simultaneously

Lights

Dual headlights, rear work light, combination stop and tail light.

Tires

Drive Tires-19.5L x 24 10 PR Industrial Lug (R4) tread puncture proof foam filled.

Steer Tires 2WD - 33 x 1 x 6 puncture proof flexport.

Steer Tires 4WD 12.5/80 x 18 10 plu Aggressive foam filled


Tread puncture proof foam filled

GENERAL DIMENSIONS

Wheelbase	96"
Overall Length	167"
Overall Width	87"
Overall Height	105"
Ground Clearance	11"
Gradeability	22%

STANDARD FEATURES

- Driver Overhead Guard Assembly with rain shield
- Walk Thru Operator Compartment
- **Deluxe Adjustable Seat with Seat Belt**
- Safety Back-Up Alarm
- **Safety Horn**
- **Drive Tire Fender (16" For Safety)**
- **Dual Hand Entry Grips (Both Sides Operator Com**partment)
- 2" Side Shift
- **Puncture Proof Drive and Steer Tires**
- Fender Mounted Box for Blocks or 2x4's









229-386-0610

229-382-8482

sales@mclifts.com

https://mclifts.com

333 Southwell Blvd Tifton, GA 31794

Check us out on Tiktok!